



EL SERIES

SELF-PROPELLED MOBILE ELEVATED WORK PLATFORM

STANDARD FEATURES

- Electric drive
- ▶ LeakGuard®
- ▶ Drive at full height indoor & outdoor
- ▶ 110V power-to-platform
- Proportional controls
- > 30A Charger
- Non-slip deck
- ▶ All motion alarm
- Flashing beacon
- ▶ Removable platform controls
- ▶ Self-locking gate
- Liftable with forklift or crane

- Dual Maintenance bars
- Onboard diagnostic system
- Manual decent cable
- Active tilt alarm
- ▶ Slide out extension
- Automatic pothole protection
- ▶ Non-marking tires
- Horn
- ► CAN communication protocol
- ▶ 2-year parts & labor warranty
- ▶ 5-year structural warranty

STANDARDS COMPLIANCE

NSI A92.20

OPTIONS

- Perimeter Lights
- Pipe Rack

EL-2645e SCISSOR

Hydraulic Tank Capacity

Battery

SPE	CIFICATIONS		
A	Working Height (3 Person Indoor/1 Person Outdoor)	32.3ft	10 m
В	Platform Height Maximum (3 Person Indoor/1 Person Outdoor)	26.3 ft	8 m
С	Platform Height Minimum	47.6 in	1.21 m
D	Ground Clearance Elevated	0.79 in	2 cm
E	Ground Clearance Lowered	4.7 in	12 cm
F	Overall Length w/Step	97.3 in	2.47 m
G	Overall Width	45 in	1.15 m
	Stowed Height (Rails Unfolded)	91 in	2.31 m
Н	Stowed Height (Rails Folded)	65.7 in	1.67 m
1	Platform Length	91 in	2.31 m
J	Platform Width	45 in	1.14 m
К	Slide Out Extension Deck Length	39.4 in	1 m
	Wheelbase	73.2 in	1.86 m
	Tires	15 x 5 in	38 x 12.7 cm

PERFORMANCE		
Rated Occupancy (Indoor/Outdoor)	3 / 1 Person(s)	
Platform Capacity	992 lbs	450 kg
Slide Out Extension Deck Capacity	330 lbs	150 kg
Gradeability	25%	
Inside Turn Radius	0 in	0 cm
Drive Speed Elevated	0.4 mph	0.6 km/h
Drive Speed Lowered	2.8 mph	4.5 km/h
Working Slope	2°/3°	
Lift Speed (Up/Down)	35 s	
Weight	5577.7 lbs	2530 kg
POWER		

7.1 gal

27 L

4 x 6V 315 Ah



