



# EL-4555XCe SCISSOR



## EL SERIES

### SELF-PROPELLED MOBILE ELEVATED WORK PLATFORM

#### STANDARD FEATURES

- ▶ Electric drive
- ▶ LeakGuard®
- ▶ Indoor & outdoor operation settings
- ▶ 110V power-to-platform
- ▶ Proportional controls
- ▶ 30A Charger
- ▶ Non-slip deck
- ▶ All motion alarm
- ▶ Flashing beacon
- ▶ Removable platform controls
- ▶ Self-locking gate
- ▶ Lifiable with forklift or crane
- ▶ Dual Maintenance bars
- ▶ Onboard diagnostic system
- ▶ Manual decent cable
- ▶ Active tilt alarm
- ▶ Slide out extension
- ▶ Automatic pothole protection
- ▶ Non-marking tires
- ▶ Horn
- ▶ CAN communication protocol
- ▶ 2-year parts & labor warranty
- ▶ 5-year structural warranty

#### STANDARDS COMPLIANCE

- ▶ ANSI A92.20

#### OPTIONS

- ▶ Perimeter Lights
- ▶ Pipe Rack

# EL-4555XCe

## SCISSOR

### SPECIFICATIONS

<b>A</b>	Working Height (2 Person Indoor)	<b>51.1 ft</b>	15.6 m
	Outdoor Working Height (1 Person Outdoor)	<b>38 ft</b>	11.6 m
<b>B</b>	Platform Height Maximum (2 Person Indoor)	<b>45.1 ft</b>	13.75 m
	Outdoor Platform Height Maximum (1 Person Outdoor)	<b>32 ft</b>	9.75 m
<b>C</b>	Platform Height Minimum	<b>63 in</b>	1.6 m
<b>D</b>	Ground Clearance Elevated	<b>0.79 in</b>	2 cm
<b>E</b>	Ground Clearance Lowered	<b>4.7 in</b>	12 cm
<b>F</b>	Overall Length w/Step	<b>109.8 in</b>	2.79 m
<b>G</b>	Overall Width	<b>55 in</b>	1.39 m
<b>H</b>	Stowed Height (Rails Unfolded)	<b>106.4 in</b>	2.7 m
	Stowed Height (Rails Folded)	<b>83.5 in</b>	2.12 m
<b>I</b>	Platform Length	<b>105.5 in</b>	2.68 m
<b>J</b>	Platform Width	<b>45.3 in</b>	1.15 m
<b>K</b>	Slide Out Extension Deck Length	<b>39.4 in</b>	1 m
	Wheelbase	<b>87.4 in</b>	2.22 m
	Tires	<b>15 x 5 in</b>	38 x 12.7 cm

### PERFORMANCE

Rated Occupancy (Indoor/Outdoor)	<b>2 / 1 Person(s)</b>	
Platform Capacity	<b>771.6 lbs</b>	350 kg
Slide Out Extension Deck Capacity	<b>330.7 lbs</b>	150 kg
Gradeability	<b>25%</b>	
Drive Speed Elevated (Proportional)	<b>0.37 mph</b>	0.6 kph
Drive Speed Lowered (Proportional)	<b>2.8 mph</b>	4.5 kph

Working Slope	<b>2° / 3°</b>	
Lift Speed (Up/Down)	<b>77 / 62 sec</b>	
Weight	<b>8818 lbs</b>	4000 kg

### POWER

Hydraulic Tank Capacity	<b>7.4 gal</b>	28 L
Battery	<b>4 x 12V 300 Ah</b>	

