

The LeakGuard™ Fluid Containment System presents users with an alternative to inconvenient and messy containment methods, including commonly used diapers. This innovative technology allows contractors to access more jobs with strict environmental and spillage regulations that require a leak prevention system.



NO MORE DIAPERS

Save time and money by eliminating the need for diapers.



110% FLUID CONTAINMENT

The LeakGuard™ tray is capable of safely retaining all of the machine's hydraulic fluid.




USER FRIENDLY

Daily pad inspection and replacement, when needed, is fast with an easy access tray.



KEEPING IT CLEAN

If a leak develops in the hydraulic cylinder, fluid is collected in the tapered cover which is installed into the base of the machine. Fluid can then be wiped off the tapered cover or the plug can be removed to allow the fluid to drip into the tray under the hydraulic pump, avoiding internal parts.



SINGLE-TRAY SYSTEM

The LeakGuard™ system retains all leaking fluid in one, easily accessible tray, saving time and preventing messy spills.




LeakGuard™ Fluid Containment System



ELECTRIC DRIVE & STEER

Hy-Brid Lifts™ are electrically driven and steered, which means only elevation uses hydraulics. This reduces the number of hydraulic connection points, which greatly minimizes the risk of any hydraulic leakage.







LEAKGUARD



